

NU-FLEX HTS




NU-FLEX HTS



Thermal Protection



Uncoated & Coated Sleeving



Uncoated braided fiberglass



Heat treated fiberglass
Saturated with acrylic binder



Option: Black, natural (silver-gray)
White, yellow, red, blue, green. Other colors upon request



Low: -70°C (-94°F)
High: 600°C (1112°F)
Insulation class: meet the requirement of class C rated at 240°C (464°F).



Options: Nu-Flex HTS-520: standard wall .020"
Nu-Flex HTS-532: heavy wall .032"



Thermal insulation
High temperature resistance
Abrasion resistance



UZIQ2 - E80713 - VW1 Rating



Nu-Flex HTS-520: MIL-Y-1140H, QPL 3190, NEMA TF2 - Type 3, ASTM E 162 - Surface flammability, Bombardier SMP 800-C Rev. 6 : Gas toxicity, ASTM E 662 : Rate of Smoke Generation, NFPA 130 specifications for transportation applications (mass transit, rail cars, locomotives)
Nu-Flex HTS-532: NEMA TF2 - Type 4
RoHS, REACH, CMRT

PHYSICAL PROPERTIES

Physical properties	Spec	Unit	Value	
Operating temperature	-	°C (°F)	-70/600 (-94/1112)	
Maximal temperature for short period	-	°C (°F)	950 (1742)	
Dielectric breakdown	-	-	grade C-3 (no dielectric value)	
Volume resistivity	-	-	10 ¹⁴ ohm-cm @ 22°C (72°F) and 500 Volts DC	
Oil resistance	-	-	no swelling or disintegration	
Fungus resistance	-	-	inert (requires no fungicide additives)	
Abrasion resistance	SAE ARP 1536	cycles	Nu-Flex HTS-520 1200	Nu-Flex HTS-532 2350
Flammability	UL 1441 VW-1	-	pass	
Fungus resistance	-	-	Inert - none at 40x	
Flammability	-	-	self-extinguishing with removal of heat source	
Surface flammability*	ASTM E 162	-	pass	
Toxic gas generation*	Bombardier SMP 800-C	-	pass	
Rate of smoke generation*	ASTM E 662	-	pass	
Caloric Content Determination	ASTM E 1354	-	pass	
Flame Propagation	ASTM C 1166 (modified)	-	pass	

*Specific to Nu-Flex HTS-520

DIMENSIONS

Designation	NEMA Size	Minimum Ø (inches)	Maximum Ø (inches)	Indicative nominal Ø	
				(inches)	(mm)
NU-FLEX HTS-520 AWG 24	AWG 24	0.020	0.027	0.024	0.61
NU-FLEX HTS-520 AWG 22	AWG 22	0.025	0.032	0.029	0.74
NU-FLEX HTS-520 AWG 20	AWG 20	0.032	0.039	0.036	0.91
NU-FLEX HTS-520 AWG 19	AWG 19	0.036	0.044	0.040	1.02
NU-FLEX HTS-520 AWG 18	AWG 18	0.040	0.049	0.045	1.14
NU-FLEX HTS-520 AWG 17	AWG 17	0.045	0.054	0.050	1.27
NU-FLEX HTS-520 AWG 16*	AWG 16	0.051	0.061	0.056	1.42
NU-FLEX HTS-520 AWG 15*	AWG 15	0.057	0.067	0.062	1.57
NU-FLEX HTS-520 AWG 14*	AWG 14	0.064	0.074	0.069	1.75
NU-FLEX HTS-520 AWG 13*	AWG 13	0.072	0.082	0.077	1.96
NU-FLEX HTS-520 AWG 12*	AWG 12	0.081	0.091	0.086	2.18
NU-FLEX HTS-520 AWG 11*	AWG 11	0.091	0.101	0.096	2.44
NU-FLEX HTS-520 AWG 10*	AWG 10	0.102	0.112	0.107	2.72
NU-FLEX HTS-520 AWG 9*	AWG 9	0.114	0.124	0.119	3.02
NU-FLEX HTS-520 AWG 8*	AWG 8	0.129	0.141	0.135	3.43
NU-FLEX HTS-520 AWG 7*	AWG 7	0.144	0.158	0.151	3.84
NU-FLEX HTS-520 AWG 6*	AWG 6	0.162	0.178	0.170	4.32
NU-FLEX HTS-520 AWG 5*	AWG 5	0.182	0.198	0.190	4.83
NU-FLEX HTS-520 AWG 4*	AWG 4	0.204	0.224	0.214	5.44
NU-FLEX HTS-520 AWG 3*	AWG 3	0.229	0.249	0.239	6.07
NU-FLEX HTS-520 AWG 2*	AWG 2	0.258	0.278	0.268	6.81
NU-FLEX HTS-520 AWG 1*	AWG 1	0.289	0.311	0.300	7.62
NU-FLEX HTS-520 5/16*	5/16"	0.313	0.334	0.324	8.23
NU-FLEX HTS-520 AWG 0*	AWG 0	0.325	0.347	0.336	8.53
NU-FLEX HTS-520 3/8*	3/8"	0.375	0.399	0.387	9.83
NU-FLEX HTS-520 7/16	7/16"	0.438	0.462	0.450	11.43
NU-FLEX HTS-520 1/2	1/2"	0.500	0.524	0.512	13.00
NU-FLEX HTS-520 5/8	5/8"	0.625	0.655	0.640	16.26
NU-FLEX HTS-520 3/4	3/4"	0.750	0.786	0.768	19.51
NU-FLEX HTS-520 7/8	7/8"	0.875	0.911	0.893	22.68
NU-FLEX HTS-520 1	1"	1.000	1.036	1.018	25.86
NU-FLEX HTS-520 1 1/8	1 1/8"	1.125	1.161	1.143	29.03
NU-FLEX HTS-520 1 1/4	1 1/4"	1.250	1.286	1.268	32.21
NU-FLEX HTS-520 1 1/2	1 1/2"	1.500	1.536	1.518	38.56

* For heavy wall designation, replace the 520 portion by 532.

PACKAGING

Standard spools, Bulk spools, Cut lengths upon request

sales@delfingen.com • www.delfingen.com

DELFINEN_NU-FLEX HTS_EN_V1.0

Data and photos for information only. Delfingen makes no warranties as to the accuracy or completeness of this information. Delfingen reserves the right to make changes in materials or processing without notifications.